

Attachment 2: Inspection Sampling Table II

Quality: Deficit Ratio (%)		Major Defects (A): 2.5 AQL Total Defects (A+B): 4.0				Inspection Level: General I				
Lot Size	Normal Inspection					Reduced Inspection				
	Sampling Size	Major (A)		Total (A+B)		Sampling Size	Major (A)		Total (A+B)	
		Acceptance Size	Rejected Size	Acceptance Size	Rejected Size		Acceptance Size	Rejected Size	Acceptance Size	Rejected Size
≤ 50	5	0	1	0	1	2	0	1	0	1
51~90	5	0	1	0	1	2	0	1	0	1
91~150	8	0	1	1	2	3	0	1	0	2
151~280	13	1	2	1	2	5	0	2	0	2
281~500	20	1	2	2	3	8	0	2	1	3
501~1200	32	2	3	3	4	13	1	3	1	4
1201~3200	50	3	4	5	6	20	1	4	2	5
≥ 3201	80	5	6	7	8	32	2	5	3	6

Notes:

1. Base stations in a batch with Lot Size equal to or less than the minimum inspection Sampling Size shall be totally inspected.
2. Inspection standards:
 - (1) Defect Level :
The defect level is comprised of major defects (marked "A") and minor defects (marked "B").
 - (2) AQL (Acceptable Quality Levels):
Major defects (A): by AQL 2.5.
Total defects (A+B): by AQL 4.0.
3. Acceptance standards:
 - (1) If any major item in the base station equipment inspection list does not conform to the rule, it shall be recorded as a major defect. If any minor item in the base station equipment inspection list does not conform to the rule, it shall be recorded as a minor defect. Accumulative major defects is noted as (A). The sum of accumulative major defects and accumulative minor defects is noted as (A+B).
 - (2) If both (A) and (A+B) don't exceed Acceptance Size, the lot can be judged qualified if the defects get revised.

- (3) If either (A) or (A+B) is more than or equal to Rejected Size, the lot shall be deemed unqualified.
 - (4) When reduced inspection is in effect, if (A) or (A+B) exceeds Acceptance Size, and both (A) and (A+B) are less than Rejected Size, the lot or batch shall be deemed acceptable if the defects were then revised just at once.
4. Switching procedures of sampling plans.
- (1) Normal to Reduced.
When normal inspection is in effect, reduced inspection shall be instituted when 2 consecutive lots or batches have been considered acceptable.
 - (2) Reduced to Normal.
When reduced inspection is in effect, normal inspection shall be instituted if any of the following occur:
 - 1. A lot or batch is rejected; or
 - 2. (A) or (A+B) exceeds Acceptance Size, and both (A) and (A+B) are less than Rejected Size.